

TRENCH BACKFILL REQUIREMENTS:

1. PROPOSED STREETS – REFER TO DETAIL TB-1 OF SECTION 31 FOR BACKFILL REQUIREMENTS ABOVE THE PIPE ZONE.
2. EXISTING STREETS – REFER TO DETAILS TB-1 AND TB-3 OF SECTION 31 FOR BACKFILL REQUIREMENTS ABOVE THE PIPE ZONE.

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR

NOTES:

BACKFILL SHALL BE MECHANICALLY CONSOLIDATED OR SHOVEL SLICED UNDER THE HAUNCHES OF THE PIPE.

IN ROCKY OR UNYIELDING SOIL, THE TRENCH SHALL BE EXCAVATED A MINIMUM OF 12" BELOW THE PIPE AND THE TRENCH WIDTH SHALL BE INCREASED BY 12".

ONE 12" WIDE STRIP OF BACKFILL TAPE SHALL BE USED FOR EVERY 12" PIPE DIAMETER OR FRACTION THERE OF.



ENVIRONMENTAL UTILITIES  
DEPARTMENT

WATER MAIN  
TRENCH AND BACKFILL

SCALE: NONE  
REVISED: JANUARY 2019  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-1

**NOTES:**

NO WATER SHALL BE DRAWN THROUGH THE BACKFLOW DEVICE UNTIL IT HAS BEEN TESTED BY THE ENVIRONMENTAL UTILITIES DEPT.



THE BACKFLOW DEVICE SHALL BE INSULATED WITH A CITY APPROVED FREEZE PROTECTION BAG

FITTINGS SHALL BE FLANGE BY FLANGE OR RESTRAINED.

BURIED NUTS AND BOLTS, AND BARE METAL SHALL BE COATED WITH BITUMINOUS MATERIAL.

PIPE AND FITTINGS SHALL BE DUCTILE IRON.

BURIED PIPE AND FITTINGS SHALL BE WRAPPED AND SEALED WITH 8 MIL POLYETHYLENE AND VINYL TAPE.



- 1) FLANGED "Y" TYPE STRAINER (SS OR DI)
- 2) OS & Y GATE VALVE (TYP.)
- 3) DOUBLE DETECTOR CHECK
- 4) CHECK VALVE
- 5) SIAMESE 45 DEGREE FDC WITH END CAPS
- 6) WATER METER
- 7) 3 1/2" THICK REINFORCED CONCRETE SLAB. WITH #4 REBAR 12" ON CENTER
- 8) SUPPORTS 2-TYP. SHALL BE BOLTED DOWN WITH A MINIMUM OF TWO BOLTS EACH
- 9) THRUST BLOCK (TYP.)
- 10) 1/4" NON CASE HARDENED CHAIN WITH BREAKAWAY LOCK BETWEEN VALVES.
- 11) VALVE TAMPER SWITCH CONDUIT TO BUILDING FIRE CONTROL ROOM

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR

	ENVIRONMENTAL UTILITIES DEPARTMENT
	<b>FIRE PROTECTION ASSEMBLY</b>

SCALE: NONE  
 REVISED: JANUARY 2017  
 DRAWN BY: R. VAN NESS  
 APPROVED BY: RICHARD PLECKER

W-2

**NOTES:**

NO WATER SHALL BE DRAWN THROUGH THE BACKFLOW DEVICE UNTIL IT HAS BEEN TESTED BY THE ENVIRONMENTAL UTILITIES DEPT.


THE BACKFLOW DEVICE SHALL BE INSULATED WITH A CITY APPROVED FREEZE PROTECTION BAG

FITTINGS SHALL BE FLANGE BY FLANGE OR RESTRAINED.

BURIED NUTS AND BOLTS, AND BARE METAL SHALL BE COATED WITH BITUMINOUS MATERIAL.

PIPE AND FITTINGS SHALL BE DUCTILE IRON.


BURIED PIPE AND FITTINGS SHALL BE WRAPPED AND SEALED WITH 8 MIL POLYETHYLENE AND VINYL TAPE.



*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR

- 1) FLANGED "Y" TYPE STRAINER (SS OR DI)
- 2) OS & Y GATE VALVE (TYP.)
- 3) DOUBLE DETECTOR CHECK
- 4) WATER METER
- 5) 3 1/2" THICK REINFORCED CONCRETE SLAB W//#4 REBAR 12" ON CENTER.
- 6) SUPPORTS 2-TYP. SHALL BE BOLTED DOWN WITH A MINIMUM OF TWO BOLTS EACH
- 7) THRUST BLOCK (TYP.)
- 8) 1/4" NON CASE HARDENED CHAIN WITH BREAKAWAY LOCK BETWEEN VALVES.
- 9) VALVE TAMPER SWITCH CONDUIT TO BUILDING FIRE CONTROL ROOM.

	ENVIRONMENTAL UTILITIES DEPARTMENT
	<b>ONSITE FIRE PROTECTION</b>
SCALE: NONE REVISED: JANUARY 2019 DRAWN BY: R. VAN NESS APPROVED BY: RICHARD PLECKER	<b>W-3</b>

**NOTES:**

NO WATER SHALL BE DRAWN THROUGH THE BACKFLOW DEVICE UNTIL IT HAS BEEN TESTED BY THE ENVIRONMENTAL UTILITIES DEPT.


THE BACKFLOW DEVICE SHALL BE INSULATED WITH A CITY APPROVED FREEZE PROTECTION BAG

FITTINGS SHALL BE FLANGE BY FLANGE OR RESTRAINED.

BURIED NUTS AND BOLTS, AND BARE METAL SHALL BE COATED WITH BITUMINOUS MATERIAL.

PIPE AND FITTINGS SHALL BE DUCTILE IRON.

BURIED PIPE AND FITTINGS SHALL BE WRAPPED AND SEALED WITH 8 MIL POLYETHYLENE AND VINYL TAPE.



SEE DETAILS  
W-15 AND W-16  
FOR VALVE

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR

- 1) FLANGED "Y" TYPE STRAINER (SS OR DI)
- 2) OS & Y GATE VALVE (TYP.)
- 3) DOUBLE DETECTOR CHECK
- 4) WATER METER
- 5) 3 1/2" THICK REINFORCED CONCRETE SLAB W/#4 REBAR 12" ON CENTER.
- 6) SUPPORTS 2-TYP. SHALL BE BOLTED DOWN WITH A MINIMUM OF TWO BOLTS EACH
- 7) THRUST BLOCK (TYP.)
- 8) 1/4" NON CASE HARDENED CHAIN WITH BREAKAWAY LOCK BETWEEN VALVES.
- 9) VALVE TAMPER SWITCH CONDUIT TO BUILDING FIRE CONTROL ROOM.

	ENVIRONMENTAL UTILITIES DEPARTMENT
--	---------------------------------------


## ONSITE FIRE PROTECTION

SCALE: NONE  
 REVISED: JANUARY 2019  
 DRAWN BY: R. VAN NESS  
 APPROVED BY: RICHARD PLECKER

W-3



CURB STAMPED "W"  
AT SERVICE LOCATION



**NOTES:**

WATER METERS SHALL BE PURCHASED THROUGH THE CITY. PURCHASE INCLUDES INSTALLATION.

INSTALL CONCRETE BLOCKING (4"x4"x 15 1/2" SOLID SLUMP BLOCK) UNDER ENTIRE UTILITY BOX PERIMETER TIGHT TO BOTTOM OF BOX NO GAPS ALLOWED

BURIED PIPE AND FITTINGS SHALL BE WRAPPED WITH 8 MIL POLYETHYLENE OR APPROVED EQUAL.

SEE TAPPING  
SADDLE DETAIL  
(W-26)

1/2" DRAIN ROCK 2" BELOW IDLER  
TO 12" BELOW METER SETTER

- 1) METER SETTER WITH IDLER
  - 2)\* N-30 UTILITY BOX WITH FL 30 METER LID FOR 1" SERVICE
  - 3) WATER METER (PURCHASED THROUGH CITY)
  - 4) CURB STOP (COMPRESSION X FIPT)
  - 5) 4" DIA. BLUE SCHEDULE 40 RISER (NOTCHED OVER PIPE AT BASE)
  - 6) 4" METER SPUD
  - 7) BRASS COUPLING (FIPT X FIPT)
  - 8) 18" BRASS NIPPLE WITH END CAP (FOR ATTACHED SIDEWALK)
  - 9) SCH. 40 PVC THROUGH PIPE EYE
  - 10) BRASS-PVC ADAPTER
  - 11) 1 1/2" PVC
  - 12) PVC END CAP
  - 13) 2"x2" RDWD. STAKE PAINTED BLUE
- \* IF LOCATED IN THE DRIVEWAY USE A B1324 BOX W/STEEL CHECKER COVER #B1324-51JH OR APPROVED EQUAL.

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR



ENVIRONMENTAL UTILITIES  
DEPARTMENT


**RESIDENTIAL 1"  
SERVICE LINE**

SCALE: NONE  
REVISED: JANUARY 2020  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-5

- 1) CONCRETE VALVE BOX (G-5 PER DETAIL W-16)
- 2) 6" CONTINUOUS BLUE SCHEDULE 40 PVC RISER (NOTCHED OVER PIPE AT BASE)
- 3) CURB STOP
- 4) METER RESETTER WITH IDLER
- 5) N-16 UTILITY BOX OR APPROVED EQUAL for 3/4" N-30 UTILITY BOX OR APPROVED EQUAL for 1"
- 6) METER (PURCHASED THROUGH CITY)
- 7) R.P TYPE BACKFLOW DEVICE
- 8) PRESSURE REGULATOR IS ALL BRASS (NOT REQUIRED FOR IRRIGATION SERVICE)

- 9) BALL VALVES
- 10) BRASS STRAINER WITH BRASS PLUG
- 11) SCH. 40 P.V.C. THROUGH PIPE EYE
- 12) INSTALL (2) UNIONS NOT CONNECTED TO PRESSURE REGULATOR
- 13) METER SPUDS
- 14) BRASS PLUG
- 15) CONCRETE COLLAR (SEE DETAIL W-16)



**NOTES:**

NO WATER SHALL BE DRAWN THROUGH THE BACKFLOW DEVICE UNTIL IT HAS BEEN TESTED BY THE ENVIRONMENTAL UTILITIES DEPT.

ALL FITTINGS AND PIPING SHALL BE BRASS BEGINNING AT CURB STOP

IF USED FOR IRRIGATION DO NOT INCLUDE PRESSURE REGULATOR.

INSTALL (3" X 5") CONCRETE BRICK UNDER PERIMETER OF UTILITY BOXES.

WATER METERS SHALL BE PURCHASED THROUGH THE CITY. PURCHASE INCLUDES INSTALLATION.

THE BACKFLOW DEVICE SHALL BE INSULATED WITH A CITY APPROVED FREEZE PROTECTION BAG.

BURIED PIPE AND FITTINGS SHALL BE WRAPPED WITH 8 MIL POLYETHYLENE OR APPROVED EQUAL.

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR



ENVIRONMENTAL UTILITIES  
DEPARTMENT

**COMMERCIAL 1"  
SERVICE LINE**

SCALE: NONE  
REVISED: JANUARY 2020  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER


W-6





**MATERIALS:**

- 1) R.P. TYPE BACKFLOW DEVICE (CITY APPROVED)
- 2) 4" THICK REINFORCED CONCRETE SLAB WITH #4 REBAR 12" ON CENTER
- 3) THRUST BLOCKS (TYP.)
- 4) SUPPORT STANDS BOLTED INTO CONCRETE
- 5) 1/4" NON-CASE HARDENED CHAIN WITH BREAKAWAY LOCK(TWO BOLTS MINIMUM)



**NOTES:**

NO WATER IS TO BE DRAWN THROUGH THE BACKFLOW DEVICE UNTIL IT HAS BEEN TESTED BY THE ENVIRONMENTAL UTILITIES DEPT.

PIPE SHALL BE DUCTILE IRON.

PIPE AND FITTINGS SHALL BE WRAPPED WITH 8 MIL. POLYETHYLENE

USE CITY APPROVED RESTRAINED JOINTS OR FLANGED SPOOLS

THE BACKFLOW DEVICE SHALL BE INSULATED WITH A CITY APPROVED FREEZE PROTECTION BAG.

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR




ENVIRONMENTAL UTILITIES  
DEPARTMENT

COMMERCIAL 3" & LARGER  
SERVICE

SCALE: NONE  
REVISED: JANUARY 2017  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-8



*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR




ENVIRONMENTAL UTILITIES  
DEPARTMENT

RESIDENTIAL WATER SERVICE

SCALE: NONE  
REVISED: JANUARY 2016  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-9

NOTE: REFER TO DETAIL W-18 FOR "WATER SERVICE TRENCH AND BACKFILL"



*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR



ENVIRONMENTAL UTILITIES  
DEPARTMENT


**RESIDENTIAL WATER SERVICE FOR  
SEPARATED SIDEWALKS**

SCALE: NONE  
REVISED: JANUARY 2016  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-10


NOTE: REFER TO DETAIL W-18 FOR "WATER SERVICE TRENCH AND BACKFILL"

**DRAIN LINE DETAIL**



**NOTES:**

- INSTALL CONCRETE BLOCKING UNDER ENTIRE PERIMETER OF VALVE BOX
- INSTALL #12 INSULATED TRACING WIRE FROM MAIN TO CURBSTOP BOX
- INSTALL SAMPLING STATION DOOR FACING TOWARD STREET
- ABOVE GROUND PIPING SHALL BE INSULATED



- 1) 3/4" COPPER SERVICE LINE POLYETHYLENE ENCASED.
- 2) 6" DIAMETER SCHEDULE 40 RISER NOTCHED OVER PIPE AT BASE)
- 3) CHRISTY TRAFFIC BOX WITH METAL LID
- 4) CURBSTOP
- 5) 3 1/2" THICK REINFORCED CONCRETE SLAB
- 6) 1" SCH. 40 PVC DRAIN TO GUTTER
- 7) 3/4" BRASS PIPE
- 8) 3/4" TO 1/2" REDUCER (BRASS)
- 9) 1/2" COPPER TUBING
- 10) (4) ANCHOR BOLTS WITH WASHERS & NUTS
- 11) INSTALL TRACING WIRE FROM MAIN TO CURB STOP. PLACE WIRE OUTSIDE THE RISER, BUT INSIDE THE BOX.

1 1/2" - 1" REDUCER

SAMPLING STATION BODY

8" - 10" DIA. CONCRETE FOR STABILITY

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR




ENVIRONMENTAL UTILITIES  
DEPARTMENT

**SAMPLING STATION**

SCALE: NONE  
REVISED: JANUARY 2016  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER


W-11



- 1) BRASS THREADED COUPLING (IF REQUIRED)
- 2) B-40 UTILITY BOX W/TRAFFIC COVER MARKED, "RSVL ARV" IF EXTENSION IS REQ. MOTAR EXTENSION JOINT INSIDE & OUT.
- 3) 3" x 5" CONCRETE BRICK UNDER ENTIRE PERIMETER OF UTILITY BOX.
- 4) CURB STOP
- 5) BRASS UNION
- 6) COMBINATION AIR / VACUUM VALVE
- 7) BRASS CAP WITH 9 DRILLED 1/16" HOLES OR APPROVED EQUAL.
- 8) USE GALVANIZED PIPE AND FITTINGS ABOVE GROUND
- 9) 1/4" TEST COCK
- 10) CONCRETE BLOCK FOR SUPPORT
- 11) THREADED BRASS PIPE

**NOTE:**  
 BURIED PIPE AND FITTINGS SHALL BE WRAPPED WITH 8 MIL POLYETHYLENE OR APPROVED EQUAL.

*Richard D. Plecker*  
 RICHARD PLECKER  
 ENVIRONMENTAL UTILITIES DIRECTOR

	ENVIRONMENTAL UTILITIES DEPARTMENT
<h2>1" AND 2" AIR RELEASE          VALVE ASSEMBLY</h2>	
SCALE: NONE REVISED: JANUARY 2017 DRAWN BY: R. VAN NESS APPROVED BY: RICHARD PLECKER	
W-12	

**NOTES:**

FITTINGS SHALL BE DUCTILE IRON

VALVES AND FITTINGS SHALL BE WRAPPED IN 8 MIL. OR THICKER POLYETHYLENE.

BURIED NUTS AND BOLTS SHALL BE COATED WITH A BITUMINOUS MATERIAL. "T" BOLT HEADS DO NOT REQUIRE COATING.

HYDRANT BOLTS SHALL BE BREAK AWAY TYPE INSTALLED NUT SIDE UP AND FILLED WITH 25 YEAR SILICONE CAULK.

VALVE SHALL BE A MINIMUM OF 15' FROM HYDRANT.

USE APPROVED RESTRAINING JOINTS FROM VALVE TO HYDRANT BURY.

MARK THE LOCATION OF THE HYDRANT WITH A BLUE REFLECTOR PLACED 1' OFF STREET CENTERLINE. HYDRANTS LOCATED AT INTERSECTIONS SHALL BE MARKED ON BOTH STREETS, PER PROVISIONS IN SECTION 84 OF THE CALTRANS SPECIFICATIONS.


HYDRANTS USED AS BLOW-OFFS SHALL HAVE THE TOP 2" PAINTED WHITE AND BE MARKED WITH AN "X".

A MINIMUM 3 FOOT CLEAR AREA SHALL BE MAINTAINED AROUND THE FIRE HYDRANT.

CITY MAINTAINED HYDRANTS SHALL BE PAINTED WITH TWO COATS SAFTEY-YELLOW.

PRIVATELY OWNED HYDRANTS SHALL BE PAINTED WHITE.

\* - HYDRANTS SHALL BE 2' BEHIND CURB WHEN THE SIDEWALK IS DETACHED.



*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR

**MATERIALS:**

- 1) CONCRETE BLOCKING
- 2) CONCRETE SUPPORT AGAINST UNDISTURBED SOIL
- 3) FIRE HYDRANT (LEAD FREE)
- 4) 12" X 12" X 12" CONCRETE COLLAR FOR STABILITY
- 5) BREAK AWAY SPOOL WITH BREAK AWAY BOLTS ON HYDRANT FLANGE ONLY
- 6) NON-BREAKAWAY BOLTS
- 7) FULLY RESTRAINED DUCTILE IRON PIPE ENTIRE LENGTH




ENVIRONMENTAL UTILITIES  
DEPARTMENT

**FIRE HYDRANT ASSEMBLY**

SCALE: NONE  
REVISED: JANUARY 2017  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-13



PRIOR TO CONNECTION TO THE CITY MAIN, THE FOLLOWING CONDITIONS SHALL BE MET:

- A. PASSED A PRESSURE TEST
- B. PASSED A CHLORINE TEST
- C. PASSED TURBIDITY TEST
- D. PASSED A BACTII TEST
- E. APPROVAL BY THE EUD INSPECTOR

NOTES:

WATER SHALL ONLY BE DRAWN INTO THE CONTRACTORS MAIN THROUGH A CITY APPROVED RP TYPE BACKFLOW DEVICE WHICH HAS BEEN TESTED AND TAGGED BY THE ENVIRONMENTAL UTILITIES DEPARTMENT.

FINAL SYSTEM COMPONENTS NECESSARY FOR TIE-IN SHALL BE PRE-CHLORINATED AND PRE-FLUSHED IN THE PRESENCE OF AN ENVIRONMENTAL UTILITIES DEPARTMENT INSPECTOR.

UPON COMPLETION OF THE CONDITIONS NOTED ABOVE AND WITH THE APPROVAL OF THE EUD INSPECTOR, CONNECTION TO THE CITY SYSTEM MAY BE MADE. THE EUD INSPECTOR SHALL BE NOTIFIED 48 HOURS PRIOR TO THE START OF WORK.

CONTRACTOR IS TO SIZE JUMPER ADEQUATELY FOR FLUSHING PURPOSES.

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR




CITY OF ROSEVILLE  
ENVIRONMENTAL UTILITIES DEPT.

CONSTRUCTION WATER DETAIL

SCALE: NONE  
REVISED: JANUARY 2017  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-14



**NOTES:**

- 1) RESTRAINT ENTIRE MANIFOLD WITH APPROVED RESTRAINT SYSTEMS.
- 2) TAPS SHALL BE MADE SUCH THAT NO DEAD END LINES RESULT.
- 3) ALL LINES 3" AND LARGER SHALL BE DIP.
- 4) AFTER THE MANIFOLD, UNDERGROUND AND ABOVE, HAS BEEN ACCEPTED, METERS SHALL BE PURCHASED THROUGH THE CITY AND INSTALLED BY CITY CREWS. WATER MAY NOT DRAWN PRIOR TO TESTING AND TAGGING THE BACKFLOW DEVICE BY THE EUD
- 5) PROVIDE A PAD WITHIN THE LIMITS OF THE BACKFLOW MANIFOLD WITH POSITIVE DRAINAGE AND A 2% MAX. SLOPE.
- 6) IN A BACKFLOW MANIFOLD CONFIGURATION THAT INCLUDES DOMESTIC AND IRRIGATION SERVICES, THE IRRIGATION SERVICE TAP SHALL BE DOWNSTREAM OF THE DOMESTIC SERVICE TAP.
- 7) PROVIDE A MINIMUM 3 FOOT SEPARATION BETWEEN BACKFLOWS IN PARALLEL.
- 8) PROVIDE A 3' MINIMUM CLEARANCE FROM TOE OR TOP OF ANY SLOPE. NO SLOPES GREATER THAN 2:1 ADJACENT TO BACKFLOW MANIFOLD. IF THE ABOVE CRITERIA IS NOT MET, A RETAINING WALL IS REQUIRED. THE RETAINING WALL SHALL BE CONSTRUCTED OF CONCRETE OR MASONRY ONLY.
- 9) PROVIDE CURB STOPS AS REQUIRED PER THESE STANDARDS.
- 10) METER LID SHALL BE STENCILLED WITH THE NUMBER ADDRESS IT SERVES. USE WHITE ENAMEL PAINT AND 2" TALL STENCILING.
- 11) A METER BYPASS WITH A LOCKING CURB STOP OR LOCKING VALVE SHALL BE REQUIRED FOR ALL DOMESTIC SERVICES 3" AND LARGER OR WHERE REQUIRED.
- 12) MANIFOLD PIPING SHALL BE A MAXIMUM DEPTH OF 6 FEET.

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR




ENVIRONMENTAL UTILITIES  
DEPARTMENT

**BACKFLOW MANIFOLD SCHEMATIC**


SCALE: NONE  
REVISED: JANUARY 2016  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-15







UNDEVELOPED AREA



PAVED AREA



LANDSCAPED AREA



GATE VALVE

### MATERIALS

- 1) CONCRETE VALVE BOX
- 2) #12 INSULATED TRACING WIRE OUTSIDE RISER
- 3) 8" RISER STOCK
- 4) RISER ALIGNER
- 5) PLASTIC BACKFILL TAPE
- 6) GATE VALVE
- 7) DUCTILE IRON TEE
- 8) CONCRETE COLLAR (SEE NOTES) \*
- 9) CONCRETE BRICK (SEE NOTES)
- 10) #4 REBAR AROUND CIRCUM. (TYP.)
- 11) VALVE EXTENSION PER SECTION 81-12.B

\* CONCRETE COLLAR SHALL BE PLACED FLUSH TO FINISH GRADE IN ALL COLLECTORS AND ARTERIALS, OPTIONAL IN ALL OTHER ROADWAYS. FINISH SURFACE SHALL BE MEDIUM BROOM FINISH WITH PATTERN PERPENDICULAR TO VEHICLE TRAVEL DIRECTION. SET COLLAR 1/8" BELOW ADJACENT FINISHED PAVEMENTS.

### NOTES:

TRACING WIRE THROUGH VALVE BOXES SHALL BE PLACED OUTSIDE OF RISER BUT INSIDE OF BOX.

TRACING WIRE SHALL BE SPLICED INSIDE THE VALVE BOX PER (W-17) AND SHALL LOOP WITHIN THE VALVE BOX WITH 18" OF SLACK WIRE

ALL GATE VALVES SHALL BE CENTERED IN A ONE PIECE RISER STOCK WITH THE USE OF A RISER ALIGNER

OPERATOR NUTS DEEPER THAN 40 INCHES FROM FINISH GRADE SHALL REQUIRE A VALVE NUT EXTENSION 2 FEET MINIMUM IN LENGTH.

VALVE BOXES LOCATED IN A PAVED AREA SHALL BE PLACED IN A 6" X 6" CONCRETE COLLAR A MINIMUM OF 3" BELOW PAVEMENT

VALVE BOXES LOCATED IN A LANDSCAPED AREA SHALL BE PLACED IN A 6" X 6" CONCRETE COLLAR AT FINISHED GRADE.

VALVE BOXES LOCATED IN AN UNDEVELOPED AREA SHALL BE PLACED IN A 12" DEEP BY 6" WIDE CONCRETE COLLAR 6 INCHES ABOVE GRADE.

INSTALL (3" X 5" CONCRETE BRICK) UNDER ENTIRE PERIMETER OF BOX.

VALVES AND FITTINGS SHALL BE WRAPPED AND SEALED IN 8 MIL POLYETHYLENE

VALVE RISOR STOCK SHALL BE A MINIMUM OF 4" INSIDE VALVE BOX AND MINIMUM 2" BELOW METAL RING.

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR


CITY OF  
**ROSEVILLE**  
CALIFORNIA

ENVIRONMENTAL UTILITIES  
DEPARTMENT

## GATE VALVE & BOX

SCALE: NONE  
REVISED: JANUARY 2020  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-16



NOTES:

1. TWIST THE WIRE A MINIMUM OF (5) TIMES ON EACH END.
2. INSTALL SPLIT BOLT CONNECTOR.
3. SOLDER WIRE
4. COVER THE ENTIRE SPLICE WITH MASTIC TAPE WRAP
5. WRAP MASTIC WITH VINYL TAPE.
6. WIRE SPLICES SHALL BE LOCATED WITHIN A VALVE BOX PER DETAIL W-16.

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR


CITY OF  
**ROSEVILLE**  
CALIFORNIA

ENVIRONMENTAL UTILITIES  
DEPARTMENT

## TRACING WIRE SPLICE

SCALE: NONE  
REVISED: JANUARY 2016  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-17



*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR


CITY OF  
**ROSEVILLE**  
CALIFORNIA

ENVIRONMENTAL UTILITIES  
DEPARTMENT

TRENCH AND BACKFILL FOR ALL  
WATER LINES 2" AND SMALLER


SCALE: NONE  
REVISED: JANUARY 2016  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-18



TEST STATION (TYPICAL)

\*FOR VALVES WELD ON FLANGE



TEST STATION BOARD (TYPICAL)

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR




ENVIRONMENTAL UTILITIES  
DEPARTMENT

INSULATING FLANGE TEST STATION



SCALE: NONE  
REVISED: JANUARY 2017  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-19


1) FILE TO BARE METAL & CLEAN OVER SURFACE





2) STRIP INSULATION FROM WIRE AND ATTACH SLEEVE



3) HOLD MOLD FIRMLY WITH OPENING AWAY FROM OPERATOR, IGNITE WITH FLINT GUN



4) REMOVE SLAG FROM CONNECTION, COVER CONNECTION WITH COMPATIBLE COATING AND CAP OVER ALL EXPOSED METAL



*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR

NOTE:  
EACH JOINT SHALL HAVE TWO  
SEPARATE WELD WIRES.




ENVIRONMENTAL UTILITIES  
DEPARTMENT

**EXOTHERMIC WELD**

SCALE: NONE  
REVISED: JANUARY 2016  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-20



*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR

NOTES:

1. DIELECTRIC FLANGE KITS SHALL BE MANUFACTURED BY F.H. MALONEY CP., CALPICO OR APPROVED EQUAL
2. PROVIDE AN INSULATING FLANGE TEST STATION FOR THE INSULATED FLANGE.



CITY OF  
**ROSEVILLE**  
CALIFORNIA

ENVIRONMENTAL UTILITIES  
DEPARTMENT

**INSULATED FLANGE**

SCALE: NONE  
REVISED: JANUARY 2015  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-21



**NOTES:**


1. THE MINIMUM STRENGTH FOR STEEL CASING SHALL BE 35,000 PSI
2. 18 MIL COAL TAR EPOXY SHALL BE APPLIED ON THE INSIDE & OUTSIDE OF THE STEEL CASING.
3. RESTRAINED PIPE WITHIN CASINGS OR BRIDGES SHALL BE FULLY EXTENDED OR "STRETCHED OUT" TO REMOVE THE SLACK BETWEEN THE JOINTS THE ENTIRE LENGTH OF THE STRUCTURE.

CASING DETAIL


*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR


TEST BOARD



	ENVIRONMENTAL UTILITIES DEPARTMENT
	CASING & TEST STATION
SCALE: NONE REVISED: JANUARY 2016 DRAWN BY: R. VAN NESS APPROVED BY: RICHARD PLECKER	W-22



CONCRETE CAP



CONCRETE ENCASEMENT

APPLICATION:

- WHERE 30" < H < 36", USE DIP ONLY
- WHERE 20" < H < 30"
  - WITH SERVICES, USE DIP AND CONCRETE CAP
  - WITHOUT SERVICES, USE DIP AND CONCRETE ENCASE
  - (WRAP DIP IN 1/2" CLOSED CELL FOAM PRIOR TO ENCASEMENT)
- WHERE H < 20", REDESIGN WATERLINE

NOTE:

THIS DETAIL SHALL BE USED ON A CASE-BY-CASE BASIS WITH THE APPROVAL OF THE EUD DIRECTOR. IN MOST CASES, THE 36" MINIMUM COVER SHALL PREVAIL.

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR


	ENVIRONMENTAL UTILITIES DEPARTMENT
---	---------------------------------------

SHALLOW WATER MAINS

SCALE: NONE  
 REVISED: JANUARY 2017  
 DRAWN BY: R. VAN NESS  
 APPROVED BY: RICHARD PLECKER

W-23





**NOTES:**

1. RESTRAINED PIPE WITHIN CASINGS OR BRIDGES SHALL BE FULLY EXTENDED OR "STRETCHED OUT" TO REMOVE THE SLACK BETWEEN THE JOINTS THE ENTIRE LENGTH OF THE STRUCTURE.

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR





ENVIRONMENTAL UTILITIES  
DEPARTMENT

**SIPHON CONCRETE ENCASEMENT**



SCALE: NONE  
REVISED: JANUARY 2020  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-24

# GMI Cover and Frame Assembly



SECTION A-A



*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR

CITY OF  
**ROSEVILLE**  
CALIFORNIA

ENVIRONMENTAL UTILITIES  
DEPARTMENT


36" MANHOLE RING AND COVER

SCALE: NONE  
REVISED: JANUARY 2017  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER


W-25

NOTES:


TO CONFORM TO AASHTO M306-05, H-20 AND H-25 EN/24 D4000.



DOUBLE STRAP  
DUCTILE IRON PIPE SADDLE



PVC PIPE SADDLE



ARV SADDLE

MATERIALS:

- 1.) DOUBLE STRAP BRASS SADDLE FOR DUCTILE IRON MAIN
- 2.) INSULATING CORPORATION STOP OR NON INSULATED CORPORATION STOP WITH NYLON BUSHING
- 3.) BRASS SADDLE FOR PVC MAIN
- 4.) ZINC CAPS ON ALL BOLTS (ONLY WITH NON-INSULATED CORPORATION STOP)
- 5.) COPPER SERVICE
- 6.) SWING JOINT (2 - 90° BRASS FITTINGS)
- 7.) CORP STOP W/COMPRESSION COUPLING
- 8.) CORP STOP W/THREADED COUPLING
- 9.) THREADED BRASS PIPE
- 10.) TRACING WIRE (FOR COMMERCIAL SERVICES ONLY)

NOTES:

WRAP CORPORATION STOP AND COPPER SERVICE A MINIMUM OF 3' WITH AN APPROVED DIELECTRIC TAPE AND POLYKEN PRIMER PER MANUFACTURER'S RECOMENDATIONS.

SADDLES SHALL BE WRAPPED IN 8 MIL POLYETHYLENE AND BACKFILLED WITH SAND.

TRACING WIRE SHALL BE REQUIRED ON ARV, HYDRANT RUNS, BLOW OFFS, SERVICES WITHOUT CONTINUOUS COPPER PIPE, AND OTHER MAJOR APPURTENANCES.

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR




ENVIRONMENTAL UTILITIES  
DEPARTMENT

**SADDLE DETAIL**

SCALE: NONE  
REVISED: JANUARY 2016  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-26

CURB STAMPED "W"  
AT SERVICE LOCATION



SEE TAPPING  
SADDLE DETAIL  
(W-26)

**NOTES:**

WATER METERS SHALL BE PURCHASED THROUGH THE CITY  
PURCHASE INCLUDES INSTALLATION.

INSTALL CONCRETE BLOCKING (4"x4"x 15 1/2" SOLID SLUMP BLOCK)  
UNDER ENTIRE UTILITY BOX PERIMETER.

BURIED PIPE AND FITTINGS SHALL BE WRAPPED WITH 8 MIL  
POLYETHYLENE OR APPROVED EQUAL.

- 1) N 36 UTILITY BOX
- 2) ANGLED METER VALVE W/PADLOCK WINGS (PACK JOINT)
- 3) WATER METER (PURCHASED THROUGH CITY)
- 4) 4" BRASS NIPPLE
- 5) DOUBLE CHECK VALVE (WATTS SERIES 719)
- 6) STREET "L" (BRASS)
- 7) 3" X 5" CONCRETE BRICK  
UNDER ENTIRE PERIMETER OF BOX.
- 8) 1/2" DRAIN ROCK 12" THICK BELOW  
METER & B.F.
- 9) 18" BRASS NIPPLE (MIN.)

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR


CITY OF  
**ROSEVILLE**  
CALIFORNIA

ENVIRONMENTAL UTILITIES  
DEPARTMENT

**DUAL WATER USE (POTABLE)  
3/4" & 1" SERVICE LINE**

SCALE: NONE  
REVISED: JANUARY 2017  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-27



- 1) MAIN VALVE, STAINLESS STEEL BODY, AMES, CLA VAL
- 2) NEEDLE VALVE, DELTRO
- 3) PRESSURE REDUCING CONTROL, AMES CP-15,
- 4) BALL VALVES, APOLLO OR HOKE
- 5) "Y" STRAINER WITH BRASS PLUG 1/4"NPT
- 6) PRESSURE SUSTAINING VALVE, AMES CP-16,
- 7) OPEN LIMIT SWITCH, MICROSWITCH
- 8) TEST COCK, MIPT 1/4" BRASS
- 9) OPENING SPEED CONTROL, DELTRO

*Richard D. Plecker*

RICHARD PLECKERD  
ENVIRONMENTAL UTILITIES DIRECTOR

NOTES:

CITY APPROVED GATE VALVES SHALL BE PLACED UP AND DOWN STREAM OF MAIN VALVE.

FITTINGS SHALL BE BRASS COMPRESSION TYPE



ENVIRONMENTAL UTILITIES  
DEPARTMENT


COMBINATION PRESSURE REDUCING AND  
PRESSURE SUSTAINING VALVE

SCALE: NONE  
REVISED: JANUARY 2016  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-28

NOTES:

- PIPE SHALL BE DUCTILE IRON FOR 3" AND LARGER.
- INSTALL (3" X 5") CONCRETE BRICK UNDER ENTIRE PERIMETER OF THE UTILITY BOX.
- PIPE AND FITTINGS SHALL BE WRAPPED WITH 8 MIL. POLYETHYLENE
- USE CITY APPROVED RESTRAINED JOINTS OR FLANGED SPOOLS
- WATER METER SHALL BE PURCHASED THROUGH THE CITY. PURCHASE INCLUDES INSTALLATION.
- USE TURBO METER FOR IRRIGATION & COMPOUND METER FOR COMMERCIAL SERVICE.



SEE DETAIL  
W-15 & W-16


MATERIALS:

- 1) REFER TO METER TABLE IN SECTION 81-16 FOR UTILITY BOX SIZING. WITH EXTENSION. MORTAR EXTENSION JOINT INSIDE AND OUT.
- 2) METER WITH STRAINER (PURCHASED THROUGH CITY)  
INSTALL IDLER SPOOL DURING INSTALLATION OF METER BOX.
- 3) RESILENT SEAT GATE VALVE (3"-6")
- 4) 2" LOCKING CURB STOP IN G-5 BOX
- 5) 2" DOUBLE STRAP BRASS SADDLE FOR DUCTILE IRON MAIN WITH 2" MIPT BY COMPRESSION ADAPTER
- 6) THRUST BLOCKS (TYP.)
- 7) 2" BYPASS PIPE MATERIAL TO BE SOFT COPPER TYPE K (STICK NOT ROLLED COPPER) AND FITTINGS TO BE BRASS COMPRESSION TYPE.
- 8) METAL TRAFFIC LID WELD MARKED "RSVL WATER"
- 9) TRACING WIRE
- 10) SEE W-16 FOR VALVE BOX AND RISER DETAIL

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR

PLAN VIEW:  
METER BYPASS




ENVIRONMENTAL UTILITIES  
DEPARTMENT

3", 4", 6", 8" COMPOUND &  
TURBO METER WITH BYPASS

SCALE: NONE  
REVISED: JANUARY 2020  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-29



*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR

	ENVIRONMENTAL UTILITIES DEPARTMENT
--	---------------------------------------

FLOW THRU DETAIL

SCALE: NONE  
 REVISED: JANUARY 2016  
 DRAWN BY: R. VAN NESS  
 APPROVED BY: RICHARD PLECKER

W-30

CHRISTY B1730 H/20 RATED UTILITY BOX EQUIV.  
 BROOKS OR EQUAL. PROVIDE GALV. STEEL  
 CHECKERED PLATE COVER, SCREW DOWN TYPE,  
 MARKED "B.O."

VALVE BOX W/LID  
 MARKED "B.O."  
 INSTALL PER W-16.

11"  $\phi$  OD X 4"  $\phi$   
 RED. FLANGE X NPT

TRANSMISSION  
 WATER MAIN

TRACING WIRE

12"  
 MIN

FLANGED  
 GATE VALVE

FXF 90°

FLANGE X FLANGE  
 SPOOL (FXF)

6"  $\phi$  FLANGED DIP AND  
 FITTINGS, SEE PLANS  
 FOR LENGTH,  
 ORIENTATION AND  
 LOCATION

4" 45 EL

4" NPT TO NSHT NIPPLE

4" NSHT CAP

F.G.

6"  
 MAX.

#4 CONT.

6" DRAIN ROCK

6"  $\phi$  FIRE HYDRANT BURY

**NOTE:**

ALL THREADED PIPE  
 FITTINGS SHALL BE  
 BRASS

CONCRETE INSTALLED  
 FOR STABILITY

*Richard D. Plecker*

RICHARD PLECKER  
 ENVIRONMENTAL UTILITIES DIRECTOR



ENVIRONMENTAL UTILITIES  
 DEPARTMENT


**TRANSMISSION MAIN  
 SUBSURFACE BLOW OFF**

SCALE: NONE  
 REVISED: JANUARY 2020  
 DRAWN BY: R. VAN NESS  
 APPROVED BY: RICHARD PLECKER

W-31







*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR

**NOTES:**

1. PRECAST CONC. UTILITY BOX (48"X48" I.D.) WITH GALV. STEEL LID CHECKERED PLATE COVER (2 PIECE SPLIT LID, DESIGNED FOR H2O LOADING) MARKED "RSVL A.R.V." (USE SS HOLD DOWN SCREWS).
2. COMBINATION AIR/VACUUM RELEASE VALVE, PIPING, AND FITTINGS SIZED AS SHOWN ON PLAN & PROFILE SHEETS. (VALVE SHALL BE FLANGED)
3. FLANGED BUTTERFLY VALVE WITH HAND WHEEL OPERATOR.
4. WSP VENT, SCH 40, GALV. AFTER FABRICATION.
5. ARV TO BE PLACED AT HIGH POINT OF PIPE AT SIDE OUTLET FLANGE.
6. RESTRAIN ALL JOINTS BETWEEN C.C.P. AND ARV. RESTRAINED MJ WITH MEGALUG GLANDS MAY BE USED IN LUE OF FLANGED FITTINGS BEYOND G.V.
7. EXPOSED NON-GALVANIZED PIPING, VALVES, AND APPUR. SHALL BE PAINTED WITH TWO PRIMER AND TWO FINISH COATS OF MACHINERY ENAMEL (COLOR TO BE SELECTED BY EUD)
8. ALL BURIED PIPE, FITTINGS, VALVES AND APPUR. SHALL BE DUCTILE IRON AND ENCASED WITH 8 MIL. POLYETHYLENE.
9. CONCRETE INSTALLED FOR STABILITY.



ENVIRONMENTAL UTILITIES  
DEPARTMENT

**3" THROUGH 6" ARV**


SCALE: NONE  
REVISED: JANUARY 2020  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

**W-33**



**NOTES**


1. SEE VALVE BONDING DETAIL FOR ADDITIONAL REQUIREMENTS.



\* NOTE: CONCRETE COLLAR SHALL BE PLACED FLUSH TO FINISH GRADE IN ALL COLLECTORS & ARTERIALS, OPTIONAL FOR ALL OTHER ROADWAYS. FINISH SURFACE SHALL BE MEDIUM BROOM FINISH WITH PATTERN PERPENDICULAR TO VEHICLE TRAVEL DIRECTION. SET COLLAR 1/8" BELOW ADJACENT FINISHED PAVEMENT.

*Richard D. Plecker*  
 RICHARD PLECKER  
 ENVIRONMENTAL UTILITIES DIRECTOR

	ENVIRONMENTAL UTILITIES DEPARTMENT
	<p style="text-align: center;"><b>24" &amp; LARGER MAINLINE VALVE</b></p>
SCALE: NONE REVISED: JANUARY 2020 DRAWN BY: R. VAN NESS APPROVED BY: RICHARD PLECKER	
<b>W-35</b>	



\* NOTE: CONCRETE COLLAR MAY BE PLACED FLUSH TO FINISHED SURFACE WITH MEDIUM BROOM FINISH PERPENDICULAR TO VEHICLE TRAVEL DIRECTION.

*Richard D. Plecker*


RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR

	ENVIRONMENTAL UTILITIES DEPARTMENT
	INSPECTION MANHOLE FOR TRANSMISSION MAINS

INSPECTION MANHOLE FOR TRANSMISSION MAINS


SCALE: NONE  
 REVISED: JANUARY 2018  
 DRAWN BY: R. VAN NESS  
 APPROVED BY: RICHARD PLECKER

W-36



**NOTES**

CONSTRUCT MANHOLE PER AWWA C208 AND C303. DESIGN PRESSURE SHALL MEET OR EXCEED PIPELINE DESIGN PRESSURE.



*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR




ENVIRONMENTAL UTILITIES  
DEPARTMENT

**INSPECTION PORT  
FOR TRANSMISSION MAINS**

SCALE: NONE  
REVISED: JANUARY 2016  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-37



**NOTES**

1. CONCRETE CAP REQUIRED FOR ALL AREAS WITH LESS THAN 36" COVER
2. CONCRETE SHALL BE 5 SACK MIX MECHANICALLY TAMPED TO ELIMINATE VOIDS.

*Richard D. Plecker*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR




ENVIRONMENTAL UTILITIES  
DEPARTMENT


**CONCRETE CAP ON SHALLOW  
C.C.P. TRANSMISSION MAIN**

SCALE: NONE  
REVISED: JANUARY 2019  
DRAWN BY: R. VAN NESS  
APPROVED BY: RICHARD PLECKER

W-38




PARALLEL INSTALLATION




PERPENDICULAR CROSSING

BASIC SEPERATION REQUIREMENTS



PARALLEL INSTALLATION



PERPENDICULAR CROSSING

NOTES:

1. THE CONTRACTOR SHALL FOLLOW THE CITY OF ROSEVILLE STANDARDS AND TITLE 22 OF THE CALIFORNIA ADMINISTRATIVE CODE FOR THE SEPARATION REQUIREMENTS BETWEEN WATER MAINS AND SANITARY SEWER MAINS GUIDELINES PREPARED BY THE STATE OF CALIFORNIA DEPARTMENT OF HEALTH SERVICES.
2. WHEN THE BASIC SEPARATION REQUIREMENTS CANNOT BE MET, THE CONTRACTOR SHALL INSTALL WATER MAINS ACCORDING TO THE SPECIAL SEPARATION REQUIREMENTS.
3. WHEN LOCATED IN ZONE "A", THE WATER MAIN SHALL BE DUCTILE IRON PIPE (DIP) OR PVC C-900 CLASS 200 PR CITY OF ROSEVILLE STANDARDS.
4. NO WATER MAINS PARALLEL TO SANITARY SEWER MAINS SHALL BE INSTALLED WITHIN ZONE "B" WITHOUT SPECIAL APPROVAL FROM THE DEPARTMENT OF HEALTH SERVICES.
5. WHEN LOCATED IN ZONE "C", THE WATER MAIN SHALL HAVE NO JOINTS WITHIN FIVE FEET (5') FROM EITHER SIDE OF THE SANITARY SEWER CROSSING AND BE DUCTILE IRON PIPE (DIP) AND CONCRETE ENCASED.
6. WHEN LOCATED IN ZONE "D", THE WATER MAIN SHALL HAVE NO JOINTS WITHIN FIVE FEET (5') FROM EITHER SIDE OF THE SANITARY SEWER CROSSING AND BE DUCTILE IRON PIPE (DIP) PER CITY OF ROSEVILLE STANDARDS.
7. WATER MAINS AND SANITARY SEWER MAINS SHALL NOT BE INSTALLED IN THE SAME TRENCH.

*Richard D. Plecker*

RICH PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR




ENVIRONMENTAL UTILITIES  
DEPARTMENT


**WATER MAIN AND SEWER  
MAIN CROSSING**

SCALE: NONE  
REVISED: JANUARY 2018  
DRAWN BY: J. CUMMINGS  
APPROVED BY: R. PLECKER





TEST STATION (TYPICAL)



TEST STATION BOARD (TYPICAL)

*Richard D. Samuelson*

RICHARD PLECKER  
ENVIRONMENTAL UTILITIES DIRECTOR



ENVIRONMENTAL UTILITIES  
DEPARTMENT

TEST STATION

SCALE: NONE  
REVISED: JANUARY 2019  
DRAWN BY: D. SAMUELSON  
APPROVED BY: RICHARD PLECKER

W-40